

# 125

## SINGLE LINER HIGH TACK MEDIA BLAST STENCIL - HAND CUT

### DESCRIPTION

Hand-cut, high quality, durable stencil coated with an advanced, high tack, water-based, pressure-sensitive, acrylic adhesive protected by an easy-release blue liner. #125 is designed and recommended for raw/unfinished wood, HDU foam-board, brick and rough stone. Not intended for use on marble, granite, or polished surfaces.

### PRODUCT APPLICATION

Caution: Water-based acrylic adhesive may transfer to pre-treated or painted surface and/or may lift the grain of wood (esp. soft woods). Remove immediately after blasting whenever possible.

### STANDARD SIZES

12.50" x 10 yards  
18.75" x 10 yards  
25" x 10 yards

### STORAGE & SHELF LIFE

*Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.*



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/20

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Adhesive</b>	High Tack / Acrylic
<b>Total Thickness (mil)</b> PSTC-133	40 (1.02mm)
<b>Total Thickness w/o Liner (mil)</b> PSTC-133	36 (0.91mm)
<b>Tensile Strength (lbs/in)</b> PSTC-131	5 (21.9 N/25mm)
<b>180° Adhesion to Steel (oz/in)</b> PSTC-101	30 (8.2 N/25mm)
<b>Elongation (% at break)</b> PSTC-131	300
<b>Punch</b>	Unpunched, Hand Cut
<b>Liner Color</b>	Blue
<b>Recommended Filler</b>	#333



**ANCHOR**  
brand stencil products