

157

SINGLE LINER MEDIUM TACK MEDIA BLAST STENCIL – MACHINE CUT

DESCRIPTION

High quality, durable stencil coated with a medium tack, rubber-based, pressure-sensitive adhesive protected by a clear polyester liner. Features a slot-hole pattern. Rubber is trimmed back 1/2" along each edge for IBM® cutters. Designed and recommended for primed / painted wood, HDU foam-board, and polished surfaces. #157 is the IBM® equivalent of #117 stencil at 30" width.

PRODUCT APPLICATION

Design centers must be taped before transferring rubber to substrate. Replaces #111 in 30" IBM® cutter applications.

STANDARD SIZES

30" x 10 yards

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/20

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	40 (1.09mm)
Total Thickness w/o Liner (mil) PSTC-133	33 (0.84mm)
Tensile Strength (lbs/in) PSTC-131	5 (21.9 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	24 (6.57 N/25mm)
Elongation (% at break) PSTC-131	300
Punch	Friction Fed and Sprocket Fed 1/2" OC
Liner Color	Clear



ANCHOR
brand stencil products